

The information and advice included in this brochure has been prepared with care. However, we are unable to accept responsibility for the results of or any damage caused during operation.

As with all metal-based products, Luxaflex® Aluminium Venetians can be subject to some variations in the slat finishes, and are considered normal, acceptable quality. Precautions should be taken to reduce exposure to harsh environmental elements, such as salt air. Even though Luxaflex Aluminium Venetians are made with a unique clutch system, preventing damage to the tilt mechanism caused by over winding the tilt wand, care during operation must still be taken.

© Copyright 2019 Hunter Douglas Limited [ABN 98 009 675 709]. ® Registered Trade Marks of Hunter Douglas Limited. 18.019.017 [07/2019]

Aluminium Venetians



Luxaflex[®]

Welcome to the Luxaflex lifestyle

Thank you for purchasing Luxaflex® Aluminium Venetians. With proper operation and care your new blinds will provide years of beauty and performance. Please review this instruction booklet thoroughly for operation and care information.

Operation

Duo-flex® operation

1. Lower the blinds.
2. Twist the wand to operate the opening and closing of the slats.
3. Twist the wand to the right to close all of the slats.
4. Twist the wand to the left to vary the opening of the slats.
5. If a different height or opening of blind desired, repeat steps 2 to 4.

Cord and wand operation

To tilt the slats:

Simply rotate the wand to tilt the slats from fully closed to any desired angle.

To lower the blind:

To lower, simply pull the cord towards the centre of the blind and lower gently.

To raise the blind:

To raise, tilt the slats to the fully opened position. Remove the bottom rail from the hold-down brackets (if fitted). Pull the lift cord towards the centre and raise the blind. To lock in position simply move the cord towards the outer edge of the blind to engage the cord lock.

Care and cleaning

Dust can be easily brushed off at regular intervals using a clean soft cloth, a feather duster or a vacuum cleaner with brush attachment.

Routine maintenance

Dusting

To dust, tilt the slats up and then down to reach the entire top and bottom surfaces.

Vacuuming

To vacuum, use the brush attachment and tilt slats up and then down to reach the entire top and bottom surfaces.

Wiping

Slats may be wiped over with warm water and a mild detergent.